

TEHNICAL DATA SHEET

CLEANEX[®] SANIT A

Solution for unclogging and sanitizing sewers

1. OVERVIEW

In the exhaust systems of sinks or floor drains, mechanical debris accumulates which, combined with the grease resulting from washing, causes them to clog and generate unpleasant odors.

CLEANEX SANIT A is a strongly alkaline solution specially designed for cleaning, unclogging and sanitizing sewage systems for household water, as well as from industrial halls.

2. WAY OF USAGE

Cleanex Sanit A is used as such by pouring a quantity of 1-2 liters directly into the sink or floor drain.

Let it act for about 30 minutes. After cleaning, it requires cleaning the circuit with plenty of hot water.

Through the reaction between the grease present on the drains and **Cleanex Sanit A**, soaps that are easily soluble in water are formed, which also attract mechanical deposits, thus unclogging the pipes.

The operation is repeated until the drain is completely unclogged.

It is not used to clean drinking water pipes.

Don't use for leaks with aluminum components!

For storage, handling and use, read and follow the instructions in the Safety Data Sheet.

Use protective rubber gloves when handling.

Contains: Sodium Hydroxide

3. TECHNICAL QUALITY CONDITIONS

No.	CHARACTERISTICS	VERIFICATION METHOD	PROVIDED
			Cleanex Sanit A
1	Appearance	visual	clear, homogeneous liquid, yellowish color
2	Relative density at 20°C	SR EN ISO 3675:2003	1,35
3	pH, 20°C	SREN ISO 10523:2012	12,5-13,5

The product is classified as a harmful preparation if swallowed! In case of ingestion, consult a doctor.

The provisions regarding work and environmental safety provided in the product safety data sheet will be respected. Don't use empty packaging for food storage.



Corrosive

PACKING: plastic drums of 1,2 kg , 5 kg.

WARRANTY PERIOD : 36 months in storage with the condition of keeping in the original sealed packaging and at temperatures <20°C in the shade.